

## SELF RETRACTING LIFELINES

# NANO-LOK™

## SELF RETRACTING LIFELINE

Nano-Lok™ is ergonomically designed for ease-of-use and is ideal for direct connection to most harnesses. At only 1.6 lbs., it's virtually unnoticeable on your back, stays out of the way and can be easily used as a lanyard replacement. Whether your application requires single or twin leg configurations, mounting to an overhead anchor or for connection directly to harness, there are more than 30 models to choose from to suit almost any application. Nano-Lok™ locks quickly—stopping a fall within inches—providing more protection at low heights. In addition, tension is always kept on the lifeline, which reduces dragging, snapping and trip falls. Both features are key safety improvements.



### SINGLE LEG ANCHORAGE CONNECTOR

Attaches directly to back of most harnesses (no separate carabiner required) with swiveling anchorage loop that limits lifeline twisting for smoother operation



### DIRECT-TO-HARNESS CONNECTION —INSTALLS DIRECTLY TO WEBBING ON MOST HARNESSES

- Leaves D-ring open for other equipment or rescue
- Provides snug fit to workers back — eliminates nuisance flopping
- Lower attachment point keeps housing at shoulder level vs. head level



### TWIN LEG ANCHORAGE CONNECTOR

Attach two SRLs directly to back of most harnesses; installs to web—leaves dorsal D-ring open for other equipment or rescue; design provides snug fit to worker's back; interchangeable SRLs allow versatility and replacement options

### AUTOMATIC QUICK-ACTIVATING ARRESTOR

Stops falling worker within inches — reduces fall distances and average arresting forces to 900 lbs. or less; replaces lanyard and improves safety

### IMPACT-RESISTANT HOUSING

High-strength housing provides maximum durability

### 100% TIE-OFF CONFIGURATION

Provides continuous fall protection and added mobility when moving from one location to another; replaces twin-leg lanyard improves safety

### IMPACT INDICATOR

Integrated shock absorber provides visual indication of a fall

### RETRACTABLE LIFELINE

6-ft. lifeline provides continuous fall protection without restrictions—keeps lifeline out of worker's way, reducing dragging, snagging and trip falls

### i-Safe™ EQUIPPED

Helps track equipment and manage safety inspection programs

### EXTREMELY COMPACT & LIGHTWEIGHT

At just 1.6 lbs., this SRL is the lightest, most compact unit on the market in its class—15% lighter and 30% smaller

### WIDE VARIETY OF CONFIGURATIONS

Provides complete jobsite versatility and flexibility

### 420 LB. WEIGHT CAPACITY

Higher capacity for operator and tools

**NOTE:** Optional twin leg fixed anchorage connector available for ExoFit™ and other fixed D-ring harnesses

Equipped with



Model Shown  
3101277

# NANO-LOK™ HOOKS AND ANCHORS SELECTION GUIDE

ANCHOR END



HOOK/LIFELINE END

		LIFELINE HOOK						ANCHORAGE TYPE						PART NUMBER	WEIGHT (LBS.)				
		A— Steel Snap Hook	B— Steel Rebar Hook	C— Aluminum Rebar Hook	D— Steel Swiveling Snap Hook	E— Aluminum Carabiner (Captive Eye)	F— Aluminum Snap Hook	A— Steel Snap Hook	B— Steel Rebar Hook	C— Aluminum Rebar Hook	G— Cab Mount	H— Single Leg Connector	I— Twin Leg Connector			J— Twin Leg Connector (Fixed)	K— Steel Carabiner	L— Aluminum Carabiner	
SINGLE LEG	CAB MOUNT	■									■						3101240	2.38	
	HARNES MOUNT (HOUSING TO HARNES)	■			■						■							3101239	2.67
		■			■						■							3101228	2.35
		■			■						■							3101253	2.64
		■			■						■							3101229	3.32
		■			■						■							3101225	1.97
		■			■						■							3101226	2.26
	HOOK MOUNT (HOUSING TO D-RING, STRUCTURE OR ANCHOR POINT)	■			■													3101227	2.92
		■			■											■		3101215	2.51
		■			■											■		3101216	2.80
■				■											■		3101217	3.48	
■				■													3101218	2.61	
■				■													3101219	3.58	
■				■													3101241	3.88	
■				■												■	3101235	1.87	
■				■													3101214	2.16	
■				■													3101236	2.81	
NO ANCHOR CONNECTOR (ANCHORAGE LOOP ONLY)	■			■													3101237	2.81	
	■			■													3101238	3.10	
	■			■													3101252	1.95	
	■			■													3101251	2.25	
	■			■													3101250	2.92	
	■			■													3101211	1.58	
	■			■													3101210	1.87	
	■			■													3101254	2.53	
	■			■													3101279	4.43	
	■			■													3101278	5.02	
TWIN LEG	HARNES MOUNT (HOUSING TO HARNES)	■			■												3101280	6.37	
	■			■													3101275	3.69	
	■			■													3101276	4.26	
	■			■													3101277	5.57	
	■			■													3101287	4.32	
	■			■													3101274	4.90	
	■			■													3101288	6.26	
	■			■													3101271	3.57	
	■			■													3101272	4.14	
	■			■													3101273	5.46	
ANCHORS	CAB AND HARNES MOUNT (ANCHORS ONLY)	■															3100089	.42	
		■															3100088	.39	
		■															3100087	.52	
		■															3100107	.41	

**A—STANDARD STEEL SNAP**  
3/4" (19 mm) gate opening



**B—FLAT STEEL REBAR**  
2-1/2" (62.5 mm) gate opening



**C—ALUMINUM REBAR**  
2-1/4" (57 mm) gate opening



**D—STEEL SWIVELING SNAP**  
3/4" (19 mm) gate opening



**E—ALUMINUM CARABINER**  
3/4" (19 mm) gate opening




**F—ALUMINUM SNAP**  
3/4" (19 mm) gate opening



**G—CAB MOUNT**  
Stainless steel bracket,  
1.63" (41.4 mm) by 4.25"  
(108 mm)



**H—SINGLE LEG CONNECTOR**  
Triple-action open/close,  
zinc-plated steel



**I—TWIN LEG CONNECTOR**  
Self locking/closing gate,  
3/4" (19 mm) opening



**J—TWIN LEG CONNECTOR, FIXED**  
Triple locking gate, 3/4"  
(19 mm) opening, required  
for ExoFit™ and other "fixed"  
D-ring harnesses



**K—Saflok™ STEEL  
CARABINER 11/16"**  
(17.4 mm) gate opening



**L—ALUMINUM CARABINER**  
3/4" (19 mm) gate opening



SELF RETRACTING LIFELINES