

ACCESSORIES

See pages 96-107 for other anchorage devices.

8102101

REMOTE POWER TAGLINE SYSTEM

Ideal for use in applications where bridge cranes or other temporary overhead obstructions exist and fall protection is needed. The system provides easy, remote access to an overhead self retracting lifeline.

- 75 ft. per minute travel speed for rapid access
- 100 ft. length—long enough to handle the tallest ceiling-to-floor application
- Accommodates up to three SRLs for added jobsite versatility
- Includes both wireless remote and corded controls for added flexibility
- Operates on standard 110 volt power for ease of installation

8102102 REMOTE POWER TAGLINE SYSTEM 220 volt power

7211856

TAGLINE FOR SRL

3/16" polypropylene rope with O-ring at one end x 50 ft. (15 m)

7211857 Tagline x 25 ft. (7.6 m)

7211858 Tagline x 35 ft. (10.6 m)



1003006

TIE-OFF ADAPTOR

Pass thru style polyester web x 6 ft. (1.8 m)

5900551

Cable pass-thru tie-off adaptor x 6 ft. (1.8 m)



CARABINERS



2000112

SAFLOK™ CARABINER

Steel carabiner, self locking/closing 3,600 lb. (16kN) gate, 11/16" (17.5 mm) opening.



2000113

SAFLOK™ CARABINER

Steel carabiner, self locking/closing 3,600 lb. (16kN) gate, 1-3/16" (30 mm) gate opening.



2000114

SAFLOK™ CARABINER

Steel carabiner, self locking/closing 3,600 lb. (16kN) gate, 2-3/16" (55.5 mm) gate opening.

LOAD ARRESTOR

Protect valuable equipment and materials with sturdy, self-contained backup load arrestors. They are designed and engineered to completely stop a dropping load if it breaks free from the main support unit.

3700300

LOAD ARRESTOR

Inertia-activated shock-absorbing brake with indicator button. Maximum load is 660 lbs. (300 kg), length of cable is 40 ft. (12.2 m)

3700400 Load Arrestor, 880 lb. (400 kg) load rating x 26 ft. (8 m)

3700801 Load Arrestor with pulley, 1,760 lb. (800 kg) load rating x 13 ft. (4 m)

3700501 Load Arrestor, 1,100 lb. (500 kg) load rating x 17 ft. (5.2 m)

