

BRIGHT WIRE ROPE SLINGS



Bright Wire Rope Slings with A1 light lube (5:1 by design API spec. 9a table 3.7)

Diameter of Wire Rope vs. standard length for Pricing

Length	1/2"	5/8"	3/4"	7/8"	1"	1-1/8"	1-1/4"
3 ft	15.75	21.10	-	-	-	-	-
4 ft	17.67	23.53	40.85	58.42	-	-	-
5 ft	19.57	25.97	44.83	63.37	90.77	141.54	-
6 ft	21.47	28.40	48.79	68.34	97.02	149.74	201.95
7 ft	23.39	30.84	52.76	73.29	103.28	157.94	214.04
8 ft	25.29	33.29	56.72	78.25	109.53	166.14	226.13
9 ft	27.20	35.73	60.68	83.22	115.73	174.34	238.22
10 ft	29.11	38.17	64.65	88.17	121.95	182.55	250.31
11 ft	31.01	40.60	68.61	93.14	128.15	190.75	262.39
12 ft	32.92	43.04	72.58	98.09	134.35	198.95	274.48
15 ft	38.64	50.36	84.47	112.97	152.99	223.55	310.75
20 ft	48.18	62.55	104.29	137.76	184.03	264.57	371.18
Std. eye size	4"x 8"	5"x 10"	6"x 12"	7"x 14"	8"x 16"	9"x 18"	10"x 20"
WLL (ton)	2.5	3.9	5.6	7.6	9.8	12	15
Weight / ft	0.46	0.72	1.04	1.42	1.85	2.34	2.89

** All wire rope slings made with EIPS, IWRC Bright Wire rope with A1 light lube with steel ferrule and Flemish roll splice complete with tag showing size, length, WLL and manufacture.

