


TIE-DOWN STRAPS

3" Winch Strap, webbing b/s: 18,000 lbs



3" Winch Strap w/-38163 chain anchor (3/8")

Working Load Limit: 6,000 lbs (2,727 kgs)
Assembly B/S: 18,000 lbs (8,181 kgs)

Part No.	O/A Strap Length	Weight (lbs)
WS312-C	12 ft.	5.6
WS316-C	16 ft.	5.9
WS320-C	20 ft.	6.2
WS325-C	25 ft.	6.6
WS330-C	30 ft.	7.0



3" Winch Strap w/-38163-5 chain anchor (5/16")

Working Load Limit: 5,000 lbs (2,272 kgs)
Assembly B/S: 15,000 lbs (6,818 kgs)

Part No.	O/A Strap Length	Weight (lbs)
WS312-CS	12 ft.	4.6
WS316-CS	16 ft.	4.9
WS320-CS	20 ft.	5.2
WS325-CS	25 ft.	5.6
WS330-CS	30 ft.	6.0



3" Winch Strap w/-18440 flat hook

Working Load Limit: 5,000 lbs (2,272 kgs)
Assembly B/S: 15,000 lbs (6,818 kgs)

Part No.	O/A Strap Length	Weight (lbs)
WS312-F	12 ft.	2.6
WS316-F	16 ft.	2.9
WS320-F	20 ft.	3.2
WS325-F	25 ft.	3.6
WS330-F	30 ft.	4.0



3" Winch Strap w/-18201 wire hook (2" x 1/2")

Working Load Limit: 5,000 lbs (2,272 kgs)
Assembly B/S: 15,000 lbs (6,818 kgs)

Part No.	O/A Strap Length	Weight (lbs)
WS312-W	12 ft.	2.6
WS316-W	16 ft.	2.9
WS320-W	20 ft.	3.2
WS325-W	25 ft.	3.6
WS330-W	30 ft.	4.0



3" Winch Strap w/-18100 wire hook (3" x 5/8")

Working Load Limit: 6,000 lbs (2,727 kgs)
Assembly B/S: 18,000 lbs (8,181 kgs)

Part No.	O/A Strap Length	Weight (lbs)
WS312-W3	12 ft.	3.6
WS316-W3	16 ft.	3.9
WS320-W3	20 ft.	4.2
WS325-W3	25 ft.	4.6
WS330-W3	30 ft.	5.0



3" Winch Strap w/-18513 D ring

Working Load Limit: 6,000 lbs (2,727 kgs)
Assembly B/S: 18,000 lbs (8,181 kgs)

Part No.	O/A Strap Length	Weight (lbs)
WS312-D	12 ft.	2.6
WS316-D	16 ft.	2.9
WS320-D	20 ft.	3.2
WS325-D	25 ft.	3.6
WS330-D	30 ft.	4.0



Colours available for 3" winch straps:
Red, Blue, Yellow (standard)

O/A = Overall Length, end to end including hook
B/S = Breaking Strength
Alternate hardware and custom lengths are available upon request

WARNING

- Hardware strength may be reduced if load path in the area of hardware is not in a straight line.
- Working load requirements should be evaluated by user before selecting appropriate hardware and strap assemblies.
- Remember, all strap assemblies or systems are as strong as its weakest component including the point of attachment.

TIE-DOWN STRAPS



RATCHET STRAPS

- All ratchet straps are made with heavy duty, wear and weather resistant load control straps.
- Complies with National Safety Code Standard 10 - Cargo Securement (NSC STANDARD 10) and Web Sling & Tie-down Association Standards (WSTDA).
 - Alternate hardware and custom lengths are available upon request.
 - Colours available for 2" ratchet straps: Blue, Yellow (std), Grey, Red, Green, White.

2" Ratchet Strap, Webbing b/s: 12,000 lbs

2" Ratchet Strap w/-18300 flat hook and 70201 ratchet buckle



Working Load Limit: 3,335 lbs (1,515 kgs)
 Assembly Breaking Strength: 10,000 lbs (4,545 kgs)

STANDARD FIXED END LENGTH - 18"

Part No.	O/A Strap Length	Weight (lbs)
RS21812-FXL	12 ft.	5.1
RS21816-FXL	16 ft.	5.4
RS21820-FXL	20 ft.	5.7
RS21825-FXL	25 ft.	6.1
RS21830-FXL	30 ft.	6.5

2" Ratchet Strap w/-18200 wire hook (7/16") and 70201 ratchet buckle



Working Load Limit: 3,335 lbs (1,515 kgs)
 Assembly Breaking Strength: 10,000 lbs (4,545 kgs)

STANDARD FIXED END LENGTH - 18"

Part No.	O/A Strap Length	Weight (lbs)
RS21812-WXL	12 ft.	5.1
RS21816-WXL	16 ft.	5.4
RS21820-WXL	20 ft.	5.7
RS21825-WXL	25 ft.	6.1
RS21830-WXL	30 ft.	6.5

2" Ratchet Strap w/-18420 twisted snap hook and 70201 ratchet buckle



Working Load Limit: 3,335 lbs (1,515 kgs)
 Assembly Breaking Strength: 10,000 lbs (4,545 kgs)

STANDARD FIXED END LENGTH - 18"

Part No.	O/A Strap Length	Weight (lbs)
RS21812-TSL	12 ft.	5.1
RS21816-TSL	16 ft.	5.4
RS21820-TSL	20 ft.	5.7
RS21825-TSL	25 ft.	6.1
RS21830-TSL	30 ft.	6.5

2" Ratchet Strap w/-18202 wire hook (3/8") and 70203 ratchet buckle



Working Load Limit: 1,666 lbs (757 kgs)
 Assembly Breaking Strength: 5,000 lbs (2,272 kgs)

STANDARD FIXED END LENGTH - 18"

Part No.	O/A Strap Length	Weight (lbs)
RS21812-WS	12 ft.	4.6
RS21816-WS	16 ft.	4.9
RS21820-WS	20 ft.	5.2
RS21825-WS	25 ft.	5.6
RS21830-WS	30 ft.	6.0

2" Ratchet Strap w/-38162 chain anchor and 70201 ratchet buckle



Working Load Limit: 3,335 lbs (1,515 kgs)
 Assembly Breaking Strength: 10,000 lbs (4,545 kgs)

STANDARD FIXED END LENGTH - 33"

Part No.	O/A Strap Length	Weight (lbs)
RS23312-C	12 ft.	7.6
RS23316-C	16 ft.	7.9
RS23320-C	20 ft.	8.2
RS23325-C	25 ft.	8.6
RS23330-C	30 ft.	9.0
RS23335-C	35 ft.	9.4
RS23340-C	40 ft.	9.8

O/A = Overall Length, Adjustable and 1 Fixed end
 Alternate hardware and custom lengths are available upon request

REFER TO FEDERAL, STATE, PROVINCIAL, INDUSTRY OR LOCAL REGULATIONS FOR PROPER TIE-DOWN METHODS.
 IT IS THE OWNER'S AND USER'S RESPONSIBILITY TO DETERMINE SUITABILITY OF A PRODUCT FOR ANY PARTICULAR USE.

Safety & Accessories
 Truck Equipment
 Flatbed Accessories
 Tiedown Straps
 Utility Tiedowns
 Auto Tiedowns
 Interior Van Products
 Slings
 Rigging Hardware
 Hardware
 Webbing
 General Information

TIE-DOWN STRAPS



WHY REPLACE THE ENTIRE RATCHET STRAP WHEN ALL YOU NEED IS THE SHORT END?

CTS tail ends are offered with a variety of end fittings so you can replace the exact ratchet that you lost or build a custom unit to suit your specific needs.

WARNING

- Always protect webbing from sharp edges of load.
- Do not attempt to use strap above rated capacity.
- Do not use strap if there are any signs of cut webbing, heat or chemical damage.

3-PLY WEBBING TAIL END

- 67% more abrasion resistant
- 30% more resistant to edge cutting

2" Replacement Tail Ends, webbing b/s: 12,000 lbs

RT218-FXL



2" Ratchet Tail End w/-18300 flat hook and 70201 ratchet buckle

Working Load Limit: 3,335 lbs (1,515 kgs)
Assembly Breaking Strength: 10,000 lbs (4,545 kgs)
Length: 18"
Weight: 3.0 lbs
Custom lengths are also available.

RT218-WXL



2" Ratchet Tail End w/-18200 wire hook and 70201 ratchet buckle

Working Load Limit: 3,335 lbs (1,515 kgs)
Assembly Breaking Strength: 10,000 lbs (4,545 kgs)
Length: 18"
Weight: 3.0 lbs
Custom lengths are also available.

RT233-C



2" Ratchet Tail End w/-38162 chain anchor and 70201 ratchet buckle

Working Load Limit: 3,335 lbs (1,515 kgs)
Assembly Breaking Strength: 10,000 lbs (4,545 kgs)
Length: 33"
Weight: 4.0 lbs
Custom lengths are also available.

TL21802-F



2" Tail End w/-18300 flat hook and 2" loop

Working Load Limit: 3,335 lbs (1,515 kgs)
Assembly Breaking Strength: 10,000 lbs (4,545 kgs)
Length: 18"
Weight: 1.0 lbs
Custom lengths are also available.

TL21802-W



2" Tail End w/-18200 wire hook and 2" loop

Working Load Limit: 3,335 lbs (1,515 kgs)
Assembly Breaking Strength: 10,000 lbs (4,545 kgs)
Length: 18"
Weight: 1.0 lbs
Custom lengths are also available.

TL23302-C



2" Tail End w/-38162 chain anchor and 2" loop

Working Load Limit: 3,335 lbs (1,515 kgs)
Assembly Breaking Strength: 10,000 lbs (4,545 kgs)
Length: 33"
Weight: 2.0
Custom lengths are also available.

Alternate hardware and custom lengths are available upon request

ALL STRAP ASSEMBLIES OR SYSTEMS ARE AS STRONG AS THEIR WEAKEST COMPONENT INCLUDING THE POINT OF ATTACHMENT. NEVER EXCEED THE WORKING LOAD LIMIT (WLL). LOADS BEYOND ITS WLL CAN RESULT IN SEVERE PERSONAL INJURY OR DEATH.

CTS