

# SHOCK ABSORBING LANYARDS



## **EZ-STOP™ II** SHOCK ABSORBING LANYARDS

EZ-Stop™ II lanyards use a controlled tearing action when subjected to fall arrest forces. They limit the average arresting forces to 900 lbs. (4kN) or less. These lanyards feature 1" polyester web construction (unless specified differently), double locking snap hooks, a durable nylon shock absorber cover and various lengths and hook options to fit your job.

### **1240406**

#### **EZ-STOP™ II 100% TIE-OFF LANYARD**

Double-leg with snap hooks at each end x 6 ft. (1.8m).



#### **EZ-STOP™ II DOUBLE-LEG LANYARDS**

**1241006** Double-leg with elastic leg and snap hooks at each end x 6 ft. (1.8 m).

**1241008** Double-leg with elastic legs, snap hook and aluminum rebar hooks at leg ends x 6 ft. (1.8 m).

**1240416** Double-leg with snap hook and aluminum rebar hooks at leg ends x 6 ft. (1.8 m).

**1240427** Double-leg with snap hook and flat steel rebar hooks at leg ends x 6 ft. (1.8 m).

**1240804** Double-leg with 7/32" vinyl covered cable and snap hooks x 6 ft. (1.8 m).

### **1240006**

#### **EZ-STOP™ II LANYARD**

Single-leg with snap hooks at each end x 6 ft. (1.8 m).

### **1240256**

#### **EZ-STOP™ II ADJUSTABLE LANYARD**

Single-leg, adjustable length with snap hooks x 6 ft. (1.8 m).



### **1240706**

#### **EZ-STOP™ II LANYARD**

Single-leg with 7/32" vinyl covered cable and snap hooks x 6 ft. (1.8 m).



### **1240906**

#### **EZ-STOP™ II LANYARD**

Elastic leg, 1" web, snap hooks at ends, x 6 ft. (1.8 m).



#### **EZ-STOP™ II SINGLE-LEG LANYARDS**

**1240077** Single-leg with snap hook and aluminum rebar hook x 6 ft. (1.8 m).

**1240211** Single-leg with snap hook and Saflok Max™ hook x 6 ft. (1.8 m).

**1240086** Single-leg with snap hook and Saflok™ steel carabiner x 6 ft. (1.8 m).

### **1240362**

#### **EZ-STOP™ II SHOCK ABSORBER**

Add in-line to a non-shock absorbing lanyard for fall arrest applications. Snap hook at one end, D-ring at other x 19.5" (50 cm).



