



POLYESTER ROUND SLINGS



Polyester Round Sling – Canadian Standard – (Weight in Pounds, Length by Foot)




High tensile, flexible and lightweight, round slings are a core of endless polyester fibers encased in a tough, single wall woven polyester cover. They are often used when highly polished, fragile or delicate loads must be lifted. The softness of the sling will lessen marring, or scratch loads. The light weight of the material, combined with its flexibility allows the slings to be quickly and safely handled by riggers.

Tags sewn on each Web Sling showing WLL, length, fabric type and manufacture.

5 to 1

CODE	WLL	4 ft	6 ft	8 ft	10 ft	12 ft	14 ft	16 ft	20 ft	25 ft				
OC-60	3 ton	16.28	24.16	32.46	40.43	48.24	56.76	66.54	80.78		6000	4800	12000	
		6-OC60X4	6-OC60X6	6-OC60X8	6-OC60X10	6-OC60X12	6-OC60X14	6-OC60X16	6-OC60X20					
OC-90	4.5 ton	21.18	32.27	43.41	52.94	64.69	75.32	93.76	107.59		9000	7200	18000	
		6-OC90X4	6-OC90X6	6-OC90X8	6-OC90X10	6-OC90X12	6-OC90X14	6-OC90X16	6-OC90X20					
OC-140	7 ton	30.43	45.66	61.31	76.18	92.07	107.57	124.98	152.16		14000	11200	28000	
		6-OC140X4	6-OC140X6	6-OC140X8	6-OC140X10	6-OC140X12	6-OC140X14	6-OC140X16	6-OC140X20					
OC-230	11.5 ton				103.91	124.01	150.48	175.21	201.51	247.45		23000	18400	46000
					6-OC230X8	6-OC230X10	6-OC230X12	6-OC230X14	6-OC230X16	6-OC230X20				
OC-320	16 ton				129.50	161.34	193.89	226.64	266.06	316.76		32000	25600	64000
					6-OC320X8	6-OC320X10	6-OC320X12	6-OC320X14	6-OC320X16	6-OC320X20				
OC-400	20 ton					232.30				459.67	580.76	40000	32000	80000
						6-OC400x10				6-OC400x20	6-OC400x25			
OC-540	27 ton					308.73				613.77	771.21	54000	43200	108000
						6-OC540x10				6-OC540x20	6-OC540x25			

Polyester Round Sling – European Standard – (Weight in Tonne, Length in Meters) **7 to 1**

Colour DIN- EN1492-2	1 meter	2 meter	3 meter	4 meter	5 meter	6 meter	8 meter	10 meter				
1 tonne	9.47		27.01						1000	800	2000	
	6-1X1RS		6-1X3RS									
3 tonne				57.24	71.42	86.23			3000	2400	6000	
				6-3X4RS	6-3X5RS	6-3X6RS						
4 tonne			57.16	75.24	94.41	112.81			4000	3200	8000	
			6-4X3RS	6-4X4RS	6-4X5RS	6-4X6RS						
5 tonne		46.49	68.02			113.15	132.66			5000	4000	10000
		6-5X2RS	6-5X3RS			6-5X5RS	6-5X6RS					
6 tonne		51.16	77.50	103.74	129.24	155.10			6000	4800	12000	
		6-6X2RS	6-6X3RS	6-6X4RS	6-6X5RS	6-6X6RS						
8 tonne					174.38	200.65	263.90		8000	6400	16000	
					6-8X5RS	6-8X6RS	6-8X8RS					
10 tonne					223.36				10000	8000	20000	
					6-10X5RS							